



ELECTRICAL SCHEDULE									
NO.	VOLTS	PH.	LOAD	HEIGHT A.F.F.	LOC.	CONN.	REMARKS		
601	120	1	15.0 A	4'-2"	WALL	DD	CONVENIENCE OUTLET		
602	120	1	15.0 A	45"	WALL	DD	CONVENIENCE OUTLET - MOUNT HORIZONTAL		
5	120	1	8.0 A	108"	DFA	J-BOX	ETC ON WALK-IN LIGHT CIRCUIT/DOOR HEATER		
5.1	120	1	VERIFY	108"	DFA	J-BOX	ETC ON WALK-IN COOLER COIL		
5.2	208	3	VERIFY	---	ROOF	J-BOX	ETC ON WALK-IN COOLER CONDENSER - VERIFY LOCATION ON ROOF		
9	208	3	6.2 A	18"	WALL	J-BOX	ETC ON DISPOSER THROUGH CONTROL PANEL		
10	208	3	VERIFY	66"	WALL	J-BOX	ETC ON DISHWASHER; INTERWIRE TO CONDENSATE FAN		
14	208	1	15.4 A	5'-0"	WALL	J-BOX	ETC ON ICE MACHINE; INTERCONNECT TO REMOTE CONDENSER		
14.1	---	---	---	---	ROOF	J-BOX	ETC ON ICE CONDENSING UNIT; VERIFY LOCATION INTERCONNECT FROM ICE MACHINE		
19	208	3	75.0 A	6"	FLOOR	J-BOX	ETC TO LOAD CENTER		
24	---	---	---	---	ROOF	J-BOX	ETC HOOD FANS; SEE EXHAUST HOOD DRAWINGS FOR DETAILS		
24.1	120	1	14.0 A	108"	DFA	J-BOX	ETC HOOD LIGHTS; SEE EXHAUST HOOD DRAWINGS FOR DETAILS		
25	120	1	20.0 A	108"	DFA	J-BOX	ETC FIRE SUPPRESSION SYSTEM; SEE EXHAUST HOOD DRAWINGS FOR DETAILS		
27	120	1	5.4 A	18"	WALL	DD	FOR REFRIGERATED EQUIPMENT STAND		
28	120	1	5.0 A	18"	WALL	DD	FOR PASTA COOKER		
32	120	1	5.4 A	18"	WALL	DD	FOR REFRIGERATED EQUIPMENT STAND		
37	---	---	---	---	ROOF	J-BOX	ETC HOOD FANS; SEE EXHAUST HOOD DRAWINGS FOR DETAILS		
37.1	120	1	14.0 A	108"	DFA	J-BOX	ETC HOOD LIGHTS; SEE EXHAUST HOOD DRAWINGS FOR DETAILS		
38	120	1	20.0 A	108"	DFA	J-BOX	ETC FIRE SUPPRESSION SYSTEM; SEE EXHAUST HOOD DRAWINGS FOR DETAILS		
40	120	1	6.0 A EACH	18"	WALL	TWO(2) DD	FOR CONNECTION OVEN		
41	208	3	30.0 A	18"	WALL	J-BOX	FOR ELECTRIC KETTLE		
43	208	3	10.0 A	4'-0"	WALL	J-BOX	ETC ON MIXER		
46	120	1	5.0 A	18"	WALL	DD	FOR UNDERCOUNTER REFRIGERATOR		
52	120	1	9.0 A	18"	WALL	DD	FOR REFRIGERATED PREP TABLE		
55	120	1	7.0 A	50"	WALL	DD	FOR SLICER; MOUNT HORIZONTAL		
57	120	1	9.0 A	18"	WALL	DD	FOR UNDERCOUNTER REFRIGERATOR		
61	208	1	30.0 A	4'-2"	WALL	DD	FOR COFFEE BREWER; VERIFY REQUIREMENTS		
62	120	1	20.0 A	4'-2"	WALL	DD	FOR TEA BREWER - VERIFY REQUIREMENTS		
66	120	1	15.0 A	12"	WALL	J-BOX	ETC TO DCD ON BLENDER STATION		
70	208	3	VERIFY	24"	WALL	J-BOX	ETC ON DISHWASHER - VERIFY REQUIREMENTS		
74	120	1	15.0 A	12"	WALL	J-BOX	ETC TO DCD ON BLENDER STATION		
75	120	1	2.3 A	18"	WALL	DD	FOR BACK BAR FREEZER		
76	120	1	6.5 A	18"	WALL	DD	FOR BACK BAR COOLER		
77	120	1	6.5 A	18"	WALL	DD	FOR BACK BAR COOLER		
78	120	1	2.0 A	18"	WALL	J-BOX	ETC; FOR PIZZA OVEN		
80	120	1	7.9 A	18"	WALL	DD	FOR REFRIGERATED PREP TABLE		
81	208	1	15.0 A	4'-6"	WALL	DD	FOR PANINI GRILL		
83	120	1	5.0 A	18"	WALL	DD	FOR UNDERCOUNTER REFRIGERATOR		

ELECTRICAL NOTES

A ALL ELECTRICAL OUTLETS SHOWN ON THIS PLAN ARE FOR FIXTURES SPECIFIED AS FURNISHED BY THE KITCHEN EQUIPMENT SUPPLIER. FOR FURTHER BUILDING ELECTRICAL REQUIREMENTS (TELEPHONES, CLOCKS, SIGNS, ETC.) SEE OTHER PLANS.

B ALL DIMENSIONS GIVEN ARE IN INCHES TO 4'-0" AND ARE FROM CENTERLINES AND/OR FINISHED WALLS. ELEVATIONS GIVEN ARE FROM FINISHED FLOOR TO CENTERLINE OF OUTLET. ALL ROUGH-INS SHOWN ARE TO BE RUN INSIDE WALLS (EXCEPT STUB-UPS). LOCATION INDICATES POINT OF EXIT FROM WALLS, CEILING OR FLOOR. ALL CONVENIENCE OUTLETS ARE TO SET HORIZONTALLY. ALL 120 VOLT OUTLETS NOT DESIGNATED WITH SPECIFIC LOADS TO BE WIRED AT 20.0 AMPS.

C ELECTRICIAN TO CONNECT ALL ELECTRICAL EQUIPMENT AND FIXTURES AND DO ANY INTERNAL WIRING REQUIRED IN THE FIXTURES AS REQUIRED BY THE SPECIFICATIONS. ALL ELECTRICAL OUTLET COVER PLATES ARE TO BE STAINLESS STEEL AND ARE TO BE FURNISHED BY THE ELECTRICIAN, AS WELL AS THE RECEPTACLE, UNLESS OTHERWISE SPECIFIED IN THE ITEM SPECIFICATIONS. ALL DISCONNECT SWITCHES ARE TO BE FURNISHED AND INSTALLED BY THE ELECTRICIAN AT TIME OF INSTALLATION.

D ALL WORK TO BE PERFORMED IN FULL ACCORDANCE WITH ALL APPLICABLE CODES RELATING TO WIRING, INSTALLATION AND WIRING OF EQUIPMENT. OMISSIONS OR ERRORS ON THE SCHEDULE DO NOT RELIEVE THE ELECTRICIAN FROM COMPLETE FINAL CONNECTION RESPONSIBILITY.

E IF ELECTRICAL OUTLETS AND/OR RECEPTACLES ARE CHANGED FROM "STUB-UP" TO "WALL-MOUNTED", THE "WALL-MOUNTED" OUTLETS AND/OR RECEPTACLES ARE TO BE SET AT 12" A.F.F.

ELECTRICAL SYMBOLS/ABBREVIATIONS	
⊕	JUNCTION BOX (J-BOX)
⊙	CONDUIT
•	STUB-UP
⊕	DUPLEX CONVENIENCE OUTLET (DD)
⊕	SINGLE CONVENIENCE OUTLET (DD)
⊕	SINGLE POWER OUTLET (208)
⊕	LIGHT INDICATOR
⊕	BREAKER PANELBOARD
⊕	SWITCH AS NOTED
⊕	MOTOR
⊕	HEATING ELEMENT
⊕	ELEVATION ABOVE FINISHED FLOOR
A	AMPERES
V	VOLTS
W	WATTS
PH	PHASE
AF	ABOVE FINISHED FLOOR
DFA	DOWN FROM ABOVE
ETC	BRANCH TO CONNECTION POINT AND CONNECT EQUIPMENT
SU	STUB UP ABOVE FINISHED FLOOR
HP	HORSE POWER
KW	KILOWATTS
DC	DIRECT CONNECTION
RES	KITCHEN EQUIPMENT SUPPLIER

Designer's & Planners

Taylor Design Group

19119 Ferry Boat Drive
Katy, Texas 77449
Ph: (713) 447-4999 Fax: (281) 856-2684

LUCA & LEONARDO

The Woodlands, Texas

REVISIONS

Date Issued For

Architect

Civil Engineer

Structural Engineer

Kitchen Designer
Taylor Design Group
Food Service Design & consulting
19119 Ferry Boat Drive
Katy, Texas 77449
TEL 713-447-4999
FAX 281-856-2684

Engineer's Seal

Sheet Title

FOODSERVICE EQUIPMENT ELECTRICAL PLAN

Project No.: 0000.00

Drawn By: WRW

Checked By:

Date: August 13, 2010

SHEET NO.

FS-3.0