

PATH OF EGRESS = 42" WIDE






FIRE EXTINGUISHER CABINET



WALL-MOUNTED FIRE EXTINGUISHER



02-16-12 ISSUED FOR BIDDING

01-25-12 ISSUED FOR PERMIT

LEGEND

- REFER TO GENERAL INFORMATION SHEET A0.0 FOR OCCUPANT LOAD AND EGRESS CALCULATIONS.
- 2. FIRE EXTINGUISHERS: COMPLY WITH PRODUCT REQUIREMENTS OF NFPA 10 AND APPLICABLE CODES, WHICHEVER IS MORE STRINGENT.

1. TYPE FE: DRY CHEMICAL TYPE FIRE EXTINGUISHERS: CAST STEEL TANK, WITH PRESSURE GAGE, CLASS A,B,C, SIZE 10.

3. FIRE EXTINGUISHER CABINETS (FEC).

1. BOX: SEMI— RECESSED 20 GAGE COLD ROLLED STEEL WITH WHITE BAKED ENAMEL FINISH. 2. TRIM: FLAT TRIM 1,3/4 INCHES WIDE BY 5/16 INCH (AT

GYPSUM BOARD, MASONRY AND TILE SURFACES). 3. DOOR: SOLID PANEL, 20 GAGE COLD ROLLED STEEL WITH WHITE

BAKED ENAMEL FINISH, MANUFACTURER'S STANDARD LATCH, CONTINUOUS (PIANO TYPE) HINGE, VERTICAL LETTERING READING "FIRE EXTINGUISHER".

GENERAL LIFE SAFETY NOTES

ARCHITECTS, LP

9575 Katy Frwy., #200 Houston, Texas 77024 tel: 713.722.7071 fax: 713.722.7072

CONSULTANTS Holste & Associates, Inc.

MEP Engineers

PROJECT NAME

Maharaja Bhog

PROJECT ADDRESS 8338 Southwest Freeway Houston, Texas 77074

PROJECT NUMBER

SHEET NUMBER

11078

FLOOR LIFE SAFETY PLAN

1/4" = 1'-0"

FLOOR LIFE SAFETY PLAN